

7. Declared performance			
Essential Characteristics	Performance	Harmonized Standard	
Reaction to Fire PN EN 13501-1	F	EN 13967:2012	
Resistance to water penetration 2kPa/24h PN EN 1928	conforming		
Resistance to impact PN EN 12691	≥400 mm		
Resistance to static loads PN EN12730	≥20kg/24h		
Tensile strength, machine direction (MD) PN EN 12311-2	≥300 N/50mm		
Tensile strength, cross machine direction (CD) PN EN ISO 12311-2	≥250 N/50mm		
Resistance to tear (with a nail), machine direction (MD) PN EN 12310-1	≥330N		
Resistance to tear (with a nail), cross machine direction (CD) PN EN 12310-1	≥400N		
Durability	Resistance to artificial ageing 2kPa/24h PN EN 1928/ PN EN 1296		conforming
	Resistance to chemicals 2kPa/24h PN EN 1928/ PN EN 1847		conforming
Hazardous substances	NPD		
Connection durability PN EN 12317-2	NPD		

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued according to EU Directive No. 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer signed by:

Wiesław Łącz

Quality Inspection Manager



PLAST MASTER

Teresa i Ryszard Sudol

ul. Polna 4b, 37-100 Łańcut
tel. 17 225 47 81, fax 17 225 69 41
NIP 8151001473, REGON 690318199

Lancut: 12.07.2016r. Wiesław Łącz