

PLAST MASTER Teresa i Ryszard Sudoł UI. Polna 4b, 37-100 Łańcut

1488 13

Declaration of Performance

No PM13/GR/2015

Greenfol 850

| Unique identification code of the product type | GREENFOL 850 | |
|--|--|--|
| 2. Intended use or uses | Geotextiles and related products, characteristics required for the drainage of function D (drainage) PN EN 13252:2002 (El 13252:2000) for use between other systems of terraces, "gre roofs" and civil engineering. | |
| 3. Manufacturer | Plast Master Teresa i Ryszard Sudoł Ul. Polna 4b 37-100 Łańcut | |
| 4. Authorised Representative | Not applicable | |
| 5. System of assessment and verification of constancy of performance as per the Attachment 5 | System 2+ | |
| 6a. Harmonized Standard. Notified Body. | PN EN 13252:2002 Instytut Techniki Budowlanej 1488. (Building Research Institute) | |

| Essential Characteristics | | Performance | Harmonized Standard | | |
|---------------------------|---|--------------------------------|--|------------|--|
| GSY | Water flow with PN EN ISO 1295 | in the plane of a product 8 | 12,3x10 ⁻³ (-0,90x10 ⁻³) m ² /s | 2012 | |
| | Tensile strength EN 10319 | , machine direction PN | 7,8 (-0,6) kN/m | | |
| | Tensile strength, cross machine direction PN EN 10319 | | 6,1 (-0,7) kN/m | 13967:2012 | |
| | Hazardous Subs | tances | NPD | EN 1 | |
| - Exp | | - Expected durability: | - Cover within 1 month after application - Expected durability: at least 25 years in natural soil of 4 <ph<9 <25°c<="" and="" td="" temperature=""></ph<9> | | |

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued according to EU Directive No. 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer signed by:

Wiesław Łącz Śliesłow Algor Quality Inspection Manager



Lancut: 08.07.2015 r. ul. Polna 4b, 37-100 Łańcut tel. 17 225 47 81, fax 17 225 69 41 NIP 8151001473, REGON 690318199