


PLAST MASTER  
Teresa i Ryszard Sudot  
Ul. Polna 4b, 37-100 Łańcut



## Declaration of Performance

No PM21/GR/2015  
Version nr 2

### Greenfol 700


1. <i>Unique identification code of the product type</i>	<b>GREENFOL 700</b>
2. <i>Intended use or uses</i>	<i>Geotextiles and related products, characteristics required for the drainage of function D (drainage) PN EN 13252:2002 (EN 13252:2000) for use between other systems of terraces, "green roofs" and civil engineering.</i>
3. <i>Manufacturer</i>	<i>Plast Master Teresa i Ryszard Sudot Ul. Polna 4b 37-100 Łańcut</i>
4. <i>Authorised Representative</i>	<i>Not applicable</i>
5. <i>System of assessment and verification of constancy of performance as per the Attachment 5</i>	<i>System 2+</i>
6a. <i>Harmonized Standard. Notified Body.</i>	<i>PN EN 13252:2002 Instytut Techniki Budowlanej 1488. (Building Research Institute)</i>



7. Declared performance			
Essential Characteristics		Performance	Harmonized Standard
GSY	Water flow within the plane of a product PN EN ISO 12958	12,3x10 <sup>-3</sup> (-0,90x10 <sup>-3</sup> ) m <sup>2</sup> /s	EN 13967:2012
	Tensile strength, machine direction PN EN 10319	6,5 (-0,5) kN/m	
	Tensile strength, cross machine direction PN EN 10319	5,2 (-0,6) kN/m	
	Hazardous Substances	NPD	
Durability		- Cover within 1 month after application - Expected durability: at least 25 years in natural soil of 4<pH<9 and temperature <25°C	

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued according to EU Directive No. 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer signed by:

Wiesław Łącz  
  
 Quality Inspection Manager

Lancut: 19.08.2015 r.


**PLAST MASTER**  
 Teresa i Ryszard Sudol  
 ul. Polna 4b, 37-100 Łańcut  
 tel. 17 225 47 81, fax 17 225 69 41  
 NIP. 8151001473, REGON 690318199